

SUBSIDIARY EQUIPMENT.

£ s. d.

Programme Controller with five minute selectivity, one programme with week-end silence device and mercury tube fitted or a separate relay 39 7 6

Additional programme with a maximum of four 5 12 6
per programme

Duration reducer, mechanical or electrical 11 5 0

Programme Controller, one minute programme, one programme only, week-end silence. fitted with mercury tube or separate relay 58 10 0

Programme Controller, half hour and quarter hour selectivity, one programme, week-end silence device, fitted with mercury tube or separate relay 27 0 0

Trickle Chargers.

A.C. trickle chargers consisting of transformer, metal rectifier, milliammeter, balancing resistance, and switching arrangements, mounted in a case, with the following ranges:—

	£	s.	d.
100 Milliamps	14	6	0
250	19	9	6
500	29	14	0
25	12	2	6

STANDARD PRICE LIST.

These Prices operative on and after 1st MARCH, 1947.

MASTER CLOCKS.

	£	s.	d.	P.T.
				£ s. d.
Standard Master Clock, half-minute impulse with 7" silvered engraved dial	34	0	9	8 10 3
Standard Master Clock, without dial	29	14	0	7 8 6
Standard Master Clock, without dial or case	28	6	6	7 1 7
Master Clock with seconds switch	53	11	0	13 7 9

WALL DIALS.

"A" Type.

Fitted with matt-white or cream dial, bronzed spun bezel and sheet glass, mounted in hardwood case (Oak or Mahogany).

	£	s.	d.	P.T.
				£ s. d.
8"	5	19	6	1 9 11
10"	6	2	6	1 10 7
12"	6	8	9	1 12 2
14"	7	16	6	1 19 2
18"	12	9	0	3 2 3
24"	19	12	3	4 18 0

"D" Type.

Fitted with matt-white or cream dial in Spun Metal Case bronze or chrome finish.

	Standard.	P.T.	Chrome.	P.T.
	£ s. d.	£ s. d.	£ s. d.	£ s. d.
6"	4 3 9	1 0 11	4 16 3	1 4 1
8"	4 6 9	1 1 8	4 19 6	1 4 10
10"	4 10 0	1 2 6	5 4 6	1 6 2
12"	4 16 0	1 4 0	5 10 0	1 7 6
18"	8 5 6	2 1 5	10 0 9	2 10 3
24"	16 7 3	4 1 10	18 16 9	4 14 2
	D/S Standard.	P.T.	D/S Chrome.	P.T.
	£ s. d.	£ s. d.	£ s. d.	£ s. d.
6"	10 9 0	2 12 3	12 0 3	3 0 1
8"	10 16 6	2 14 2	12 9 0	3 2 3
10"	11 5 0	2 15 3	12 18 6	3 4 8
12"	12 0 0	3 0 1	13 15 6	3 9 0
18"	20 12 6	5 3 2	23 14 9	5 18 8
24"	40 18 3	10 4 7	47 1 6	11 15 5

Spray Finish 7/6 extra up to 12". 12/6 extra over 12"

"E" Type.

Fitted with matt-white or cream dial in Bakelite Case, finished Oak, Mahogany, Black or Walnut.

Standard.	P. T.	D/S	£ s. d.	£ s. d.	£ s. d.	P. T.
10"	4 10 0	1 2 6	11 5 0	2 16 3		
12"	4 16 0	1 4 0	12 0 0	3 0 0		

"F" Type.

Fitted with matt-white or cream dial, Arabic figures only, in octagonal bakelite frame, finished Mahogany, black or Walnut.

P. T.	£ s. d.	£ s. d.
8"	4 6 9	1 1 8

C. M. Type.

Exterior wall clock. Cast-iron case with enamelled cast-iron dial, having raised black hour chapters and minute divisions, hands protected by glass, movement housed in cast-iron box. Complete assembly hermetically sealed, water and air tight, fume, dust and steam proof.

P. T.	£ s. d.	£ s. d.
12"	8 8 9	2 2 2
18"	13 17 6	3 9 5
24"	20 17 6	5 4 4
30"	28 17 6	7 4 4

C. M. O. Type.

As C.M. type dial, but fitted with opal dial, suitable for internal illumination.

P. T.	£ s. d.	£ s. d.
18"	13 0 0	3 5 0
24"	17 0 0	4 5 0
30"	31 13 0	7 18 9

"C" Type.

Frame and dial consist of a single sheet stamping, high temperature vitreous enamelled, the hands protected by glass. Specially designed for use in workshops.

Standard.	P. T.	D/S	£ s. d.	£ s. d.
12"	5 7 6	1 6 11	13 8 9	3 7 2
18"	10 0 0	2 10 0	25 0 0	6 5 0

A/I Type.

Insertion type dial fitted with matt-white or cream dial in heavy cast bezel with bevelled plate glass.

P. T.	£ s. d.	£ s. d.
6"	6 6 6	1 11 8
8"	7 8 6	1 17 1
10"	8 10 6	2 2 8
12"	9 7 0	2 6 9
14"	11 0 0	2 15 0
18"	15 5 6	3 16 5
24"	19 16 0	4 19 0

A/IS Type.

Insertion type dial, as "A/I" type, but fitted with circular spun bezel instead of heavy cast bezel.

P. T.	£ s. d.	£ s. d.
6"	4 6 3	1 1 7
8"	4 17 9	1 4 5
10"	5 6 6	1 6 8
12"	5 12 0	1 8 0
14"	6 12 0	1 13 0
18"	10 15 0	2 13 9

B/I Type.

Insertion type dial, fitted with hand engraved silvered dial, having heavy cast bezel with bevelled plate glass.

P. T.	£ s. d.	£ s. d.
6"	8 3 9	2 0 11
8"	9 8 9	2 7 2
10"	10 17 6	2 14 5
12"	11 13 9	2 18 5
14"	15 0 6	3 15 2
18"	20 14 9	5 3 8
24"	31 12 6	7 18 2